

REV.	ECN NO.	DESCRIPTION	DRAW	APPD.	DATE
A	---				



- NOTES:
SPECIFICATION:
1. CURRENT RATING: 5.0A MAX
 2. VOLTAGE: 100 VAC
 3. TEMPERATURE RANGE: -30 °C - 85 °C
 4. CONTACT RESISTANCE: 40 MILLIONHM MAX
 5. INSULATION RESISTANCE: 100 MEGOHMS MIN
 6. LNSERTION FORCE: 5N-20N
 7. UNMATING FORCE: 8N-20N
 8. DURABILITY: 10,000 CYCLES

受控文件

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND			VBUS	CC1	D+	D-	SBU1	VBUS			GND
GND			VBUS	SBU2	D-	D+	CC1	VBUS			GND
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1

BOM				品名规格
序号	名称	料号	用量	
1	外壳		1	Typec立插 外壳 SUS304 T=0.30mm
2	Molding 3		1	Typec立插 SMT 16PIN Molding C7025 LCP黑色 半成品
2.1	Molding 1		1	Typec立插 SMT 16PIN Molding A C7025 LCP黑色
2.2	Molding 2		1	Typec立插 SMT 16PIN Molding B C7025 LCP黑色
2.3	卡勾		1	Typec立插 16PIN 卡勾 SUS301 T=0.15mm

 深圳市兴烨电子有限公司 ShenZhen XingYe Electronics co., Ltd			Series Name :		
			Product Name :		
TOLERANCE			TYPE-CF-16P立贴H9.3		
X.X ±0.30	X.° ±2°	APPD: 陈爱光			
.XX ±0.20	.X° ±1°	Part NO: UCZ27495			
.XXX ±0.10	.XX° ±0.5°	CHED: 施立敏			
UNITS	mm	DRAW: 马洪飞			
			SCALE 1:1	SHEET 1/1	REV. A1