

REV.	ECN NO.	DESCRIPTION	DRAW	APPD	DATE
A	---				



受控文件

Specification:

Current rating: 1,5PIN 1.8A Max/2,3,4PIN 1A Max.

Contact resistance: 30 mΩ Max.

Insulation resistance: 100 MΩ Min.

Total mating force: 3.57 Kgf Max.

Total unmating force: 1.0 Kgf Min.

Temperature range: -30°C~80°C

RECOMMENDED PCB LAYOUT PCB图仅供参考

MKF26021	MICRO-5P 全贴带柱平口铜雾锡编带
MKF26022	MICRO-5P 全贴带柱平口铜镀镍编带
MKF26023	MICRO-5P 全贴带柱平口不锈钢雾锡编带
MKF26024	MICRO-5P 全贴带柱平口不锈钢镀镍编带



TOLERANCE			
X.X	±0.30	X.°	±2°
.XX	±0.20	.X°	±1°
.XXX	±0.10	.XX°	±0.5°
UNITS	mm		

APPD: 陈爱光

CHED: 施立敏

DRAW: 马洪飞

Series Name :
MICRO-5P 全贴带柱平口编带

Product Description :

Part NO:



SCALE	SHEET	REV.
1:1	1/1	A1

No.	Pare Name	Number	Material	Remarks
3	Shell	1PCS	copper alloy/SUS304	t=0.25mm
2	Contacts	5PCS	copper alloy	t=0.20mm
1	Housing	1PCS	LCP	UL94v-0

