

REV.	ECN NO.	DESCRIPTION	DRAW	APPD.	DATE
A	---				

SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material: LCP UL94V-0
PIN brass Tin-plated
Solder tad brassTin-plated

受控文件

PIN数	料号	尺寸			
		A	B	C	D
2P	TZL24278	1.25	4.45	5.25	3.20
3P	TZL24279	2.50	5.70	6.50	4.45
4P	TZL24280	3.75	6.95	7.75	5.70
5P	TZL24281	5.00	8.20	9.00	6.95
6P	TZL24282	6.25	9.45	10.25	8.20
7P	TZL24283	7.50	10.70	11.50	9.45
8P	TZL24284	8.75	11.95	12.75	10.70
9P	TZL24285	10.00	13.20	14.00	11.95
10P	TZL24286	11.25	14.45	15.25	13.20
11P	TZL24287	12.50	15.70	16.50	14.45
12P	TZL24288	13.75	16.95	17.75	15.70
13P	TZL24289	15.00	18.20	19.00	16.95
14P	TZL24290	16.25	19.45	20.25	18.20
15P	TZL24291	17.50	20.70	21.50	19.45
16P	TZL24292	18.75	21.95	22.75	20.70

深圳市兴烨电子有限公司
ShenZhen XingYe Electronics co., Ltd

TOLERANCE		
XX ±0.30	X° ±2°	APPD: 陈爱光
.XX ±0.20	.X° ±1°	CHED: 施立敏
.XXX ±0.10	.XX° ±0.5°	DRAW: 马洪飞
UNITS	mm	

Series Name :
1.25间距 卧式贴片无耳系列

Product Name :

Part N0:

SCALE	SHEET	REV.
1:1	1/1	A1

