

1 2 3 4 5 6 7

REV.	ECN NO.	DESCRIPTION	DRAW	APPD.	DATE
A	---				

A B C D E

1.MECHANICAL PERFORMANCE,
1-1.INSERTION FORCE: 0.5~2.0kgf.
1-2.REMOVAL FORCE: 0.6kgf~2.04kgf.
1-3.DURABILITY: 5000 CYCLES.
2.ELECTRICAL PERFORMANCE,
2-1. CURRENT RATING:3.0A
VOLTAGE RATING:5.0V
2-2. LLCR:
VBUS & GND PINS AND OTHER PINS: 40mΩ/PIN MAX.
SHIELD: 50mΩ/MAX.
LLCR MAX. CHANGE OF ALL PINS: 10mΩ.
2-3.INSULATION RESISTANCE: 100MΩ MIN
2-4.DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1 MINUTE.
3. ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -25°C~+85°C.
4.IR REFLOW:
THE PEAK TEMPERATURE ON THE BOARD SHALL
BE MAINTAINED FOR 10 SECONDS AT 260°C.

RECOMMEND P.C.B LAYOUT (COMPONENT SIDE)
TOLERANCE FOR PCB LAYOUT IS ±0.05

受控文件

PIN ASSIGNMENTS				4	Front shell	Stainless steel	Ni/SN plated
A5	CC1	B12	GND	3	Mid plate	Stainless steel	
A9	VBUS	B9	VBUS	2	Contact	Copper alloy	Au/Ni plated
A12	GND	B5	CC2	1	Housing	LCP	Black
PIN	SIGNAL NAME	PIN	SIGNAL NAME	NO.	Part name	Material	Remarks

Series Name :
Product Name :
TYPE-CF-6P板上四脚插L6. 8垫高1. 6编带
Part NO: UCZ27628
SCALE 1:1
SHEET 1/1
REV. A1

深圳市兴烨电子有限公司
ShenZhen XingYe Electronics co., Ltd

TOLERANCE
X.X ±0.30 X° ±2°
.XX ±0.20 .X° ±1°
.XXX ±0.10 .XX° ±0.5°
UNITS mm

APPD: 陈爱光
CHED: 施立敏
DRAW: 马洪飞