

PIN数	料号	尺寸	
		A	B
2P	TZD24605	3.0	9.6
3P	TZD24606	6.0	12.6
4P	TZD24607	9.0	15.6
5P	TZD24608	12.0	18.6
6P	TZD24609	15.0	21.6
7P	TZD24610	18.0	24.6
8P	TZD24611	21.0	27.6
9P	TZD24612	24.0	30.6
10P	TZD24613	27.0	33.6
11P	TZD24614	30.0	36.6
12P	TZD24615	33.0	39.6



1. Current Rating: 3.5A AC, DC
2. Voltage Rating: 250V AC, DC
3. Temperature Range: -25°C ~ +85°C
4. Contact Resistance: 20mΩ Max
5. Insulation Resistance: 1000MΩ Min
6. Withstanding Voltage: 1000V AC/minute
7. Material: LCP UL94V-0

PIN Material: brass Matte-plated
Available in 02 through 12 Circuits.

 深圳市兴烨电子有限公司 ShenZhen XingYe Electronics co., Ltd			Series Name : 30004-43650单排3.0-nP立贴带扣								
TOLERANCE			Product Pescription :								
X.X ±0.30	X.* ± 2'	APPD: 姚人凤	Part N0:  <table><tr><td>SCALE</td><td>SHEET</td><td>REV.</td></tr><tr><td>1:1</td><td>1/1</td><td>A1</td></tr></table>			SCALE	SHEET	REV.	1:1	1/1	A1
SCALE	SHEET	REV.									
1:1	1/1	A1									
.XX ±0.20	.X.* ± 1'	CHED: 施立敏									
.XXX ±0.10	.XX.* ±0.5'	DRAW: 马洪飞									
UNITS	mm										